

NMSU POP Master Field Operations Checklist

Version: Consolidated 1.0 | Modules Covered: 1-5

Date: _____ Location: _____
Staff: _____

1. Safety & PPE Protocols (Universal)

- Personal Safety:**
 - Hard hats (at height)
 - Safety glasses
 - Steel-toed boots
 - Work gloves are mandatory.
 - Never work alone; a partner is required for maintenance and transport.
- Electrical Safety:**

Ensure main disconnect is OFF before maintenance. Remove metallic jewelry. Do not bridge battery terminals. 48V DC systems can arc.
- Site Safety:**

Verify trailer is level, stable, and >500ft from the main building with clear line-of-sight. Avoid overhead power lines.

2. Mobility & Deployment (Moving the POP)

Pre-Transport & Hitching

- Shutdown:**
 - Turn off Main Disconnect and Cerbo GX.
 - Disconnect all external sensors and retract stabilizing jacks.
- Hitching:**

Use a 2-inch ball. Ensure coupler is fully seated and locked. Cross safety chains under the tongue (do not twist).
- Connections:**

Connect breakaway cable and 7-way light plug. Test brake lights, turn signals, and markers.
- Transport:**

Max speed 55 mph. Check mirrors frequently for sway.

Site Setup

- Positioning:**

Orient trailer for optimal solar exposure and wireless line-of-sight.
- Stabilization:**

Deploy jacks until trailer is perfectly level. Chock wheels.
- Reconnect:**

Connect solar panels and battery banks before powering on the load.



3. Power Systems (Solar & Battery)

Daily Inspection Criteria

Voltage Check:

Nominal voltage should be 48V (Range: 47-49V acceptable).

Charge Level:

Morning >80%; Evening (target) 100%. Critical low is <60%.

Physical Check:

- Solar panels clean/debris-free.
- Battery terminals corrosion-free.
- Inverter cooling vents clear.

Temperature:

Normal operating range 20-40°C. Warning at >50°C.

Troubleshooting Power

Low Charge (<50%):

- Reduce non-essential loads immediately.
- Check for panel shading/dirt.
- Verify MPPT is tracking.

High Temp (>50°C):

- Ensure enclosure ventilation is clear.
- Reduce load.
- Contact ACES IT.

4. Wireless Alignment & Connectivity

Alignment Procedure

Coarse Alignment:

Visually point LiteBeam toward the main building sector antenna using binoculars/compass.

Fine Tuning:

Adjust Azimuth (Left/Right) and Elevation (Up/Down) in small increments (2-5 degrees) while monitoring signal dBm.

Verification:

Lock antenna position when signal is maximized.

Signal Strength Reference

Strength (dBm)	Status	Action
-30 to -50	Excellent	Optimal target: Lock down equipment
-50 to -70	Good	Acceptable for most applications
-70 to -90	Fair	Monitor closely; may fail in bad weather
> -90	Poor	Re-align immediately
Latency	< 50 ms	High fluctuations / Packet loss



Connectivity Check: Verify data throughput (>10 Mbps download), acceptable latency (<50 ms), and no packet loss.

5. Research Operations & Data Integrity

Daily System Health

Data Flow:

Verify IoT devices, sensors, network equipment, and cameras are reporting to the main office.

Monthly Performance Review

Uptime:

Target >98% (max 7 hours downtime/month).

Storage:

Verify local and remote data storage capacity is adequate.

Maintenance:

Log all downtime incidents and root causes.

6. Quick Reference: Technical Specs & Contacts

System Specifications

Parameter	Normal Range	Critical/Failure
Battery Voltage	47V - 49V	< 45V or > 50V
Battery Temp	20°C - 40°C	> 50°C
System Load	< 40A	> 60A
Wireless Signal	-30 to -70 dBm	> -90 dBm
Latency	< 50 ms	High fluctuations / Packet loss

Key Contacts

Emergency/Fire:

- Call 911 Immediately

Wireless/IT, Power, or Trailer Issues:

- ACES IT | (575) 646-3305 | aces_help@nmsu.edu

ASC On-Site Issues:

- Contact the local ASC Director or Manager

Sign-Off Inspected By: _____ Date: _____

Status: Operational Issues Found



<https://agit.nmsu.edu/projects/pop-training.html>



575-646-3305



aces_help@nmsu.edu